



AIR NOZZLE SILVENT 707 C

Item number: 07070149328, 07070249328

- **Stainless steel slot nozzle**

SILVENT 707 C: with aerodynamic slots to optimize compressed air consumption and minimize the noise level. The extra slot nozzle in the center accelerates air velocity and increases the blowing force. Suitable for applications that require a greater concentration of force in the center of the object to be cleaned, dried, etc.

Technical data

Replace open pipe Ø (mm)	12
Blowing force (N)	19.2
Air consumption (Nm ³ /h)	120
Sound level (dB(A))	93
Nozzle technology	Slot
Material (nozzle)	1.4305 (303)
Connection	G 1/2"
Connection type	Female
Weight (g)	46
Max temp (°C)	400
Max op. pressure (MPa)	1.0

Benefits when replacing an open pipe

Replace open pipe Ø (mm)	12	
Noise reduction	23 [dB(A)]	80%
Energy savings	146 [Nm ³ /h]	55%

Material specification: EN 1.4305

Blowing properties at different pressures

Pressure (kPa)	200	400	600	800	1000
Blowing force (N)	8.1	15.3	23.6	31.0	38.7
Air consumption (Nm ³ /h)	62.7	103.3	145.0	183.5	224.0
Sound level (dB(A))	85.8	91.4	94.8	98.1	99.8

Blowing coverage (mm)

