



AIR BLOW GUN SILVENT 5920

Item number: 05920139272, 05920239272

- **Flat nozzle (zinc)**

SILVENT 5920: with a flat nozzle for applications where you want the air stream to strike a wider surface for quick and efficient blow-off. This low-noise nozzle is made of zinc and its outlet ports are protected against external forces by fins.

Technical data

Replace open pipe Ø (mm)	6
Blowing force (N)	5.5
Air consumption (Nm ³ /h)	30
Sound level (dB(A))	81
Nozzle technology	Slot
Material (nozzle)	Zn
Connection	G 1/4"
Connection type	Female
Weight (g)	264
Max temp (°C)	70
Max op. pressure (MPa)	0.7

Benefits when replacing an open pipe

Replace open pipe Ø (mm)	6	
Noise reduction	21 [dB(A)]	77%
Energy savings	37 [Nm ³ /h]	55%

Material specification: Delrin 100P BK602, NBR 70, EN 1.0718, EN 10305-1, Fzb, EN 1.4305 Zn ZP0410 EN 12844

Blowing properties at different pressures

Pressure (kPa)	200	400	600
Blowing force (N)	2.0	4.3	7.0
Air consumption (Nm ³ /h)	12.0	25.0	38.0
Sound level (dB(A))	72.0	79.1	83.3